

39-7.02 Seal Coat

A fog seal coat shall be applied to the surface of the asphalt concrete a minimum of five (5) days after paving and before acceptance of the work.

SECTION 40

PORTLAND CEMENT CONCRETE PAVEMENT
(Shall Apply Without Modification)

SECTION 41

PAVEMENT SUBSEALING AND JACKING
(Shall Apply Without Modification)

SECTION 42

GROOVE AND GRIND PAVEMENT
(Shall Apply Without Modification)

SECTIONS 43 through 48
(Blank)

SECTION 49

PILING
(Shall Apply Without Modification)

SECTION 50

PRESTRESSING CONCRETE
(Shall Apply Without Modification)

SECTION 51

CONCRETE STRUCTURES

51-1.02 Minor Structures

Minor concrete structures shall be cast in place unless otherwise authorized by the Engineer.

SECTION 52

REINFORCEMENT

(Shall Apply Without Modification)

SECTION 53

SHOTCRETE

(Shall Apply Without Modification)

SECTION 54

WATERPROOFING

(Shall Apply Without Modification)

SECTION 55

STEEL STRUCTURES

(Shall Apply Without Modification)

SECTION 56

SIGNS

56-2.06 Measurement

Roadside signs shall be measured by the unit from actual count.

SECTION 57

TIMBER STRUCTURES

(Shall Apply Without Modification)

SECTION 58

PRESERVATIVE TREATMENT OF LUMBER, TIMBER AND PILING

(Shall Apply Without Modification)

SECTION 59

PAINTING

(Shall Apply Without Modification)

SECTION 60

(Blank)

SECTION 61

CULVERT AND DRAINAGE PIPE JOINTS

(Shall Apply Without Modification)

SECTION 62

ALTERNATIVE CULVERTS

(Shall Apply Without Modification)

SECTION 63

CAST-IN-PLACE CONCRETE PIPE

(Shall Apply Without Modification)

SECTION 64

PLASTIC PIPE

(Shall Apply Without Modification)

SECTION 65

REINFORCED CONCRETE PIPE

65-1.02A(1) Circular Reinforced Concrete Pipe (Designated or Selected by Class)