

SECTION 27

CEMENT TREATED BASES
(Shall Apply Without Modification)

SECTION 28

LEAN CONCRETE BASE
(Shall Apply Without Modification)

SECTION 29

TREATED PERMEABLE BASES
(Shall Apply Without Modification)

SECTION 30 through 36
(Blank)

SECTION 37

BITUMINOUS SEALS
(Shall Apply Without Modification)

SECTION 38
(Blank)

SECTION 39

ASPHALT CONCRETE

39-2.02 Aggregate

The aggregate for the surface course shall conform to the grading and quality requirements of ½" maximum, medium grading, Type B asphalt concrete.

The aggregate for the base course shall conform to the grading and quality requirements of ¾" maximum, medium grading, Type B asphalt concrete.

39-4.02 Prime Coat and Paint Binder

Prime coats will not be required.

39-7.02 Seal Coat

A fog seal coat shall be applied to the surface of the asphalt concrete a minimum of five (5) days after paving and before acceptance of the work.

SECTION 40

PORTLAND CEMENT CONCRETE PAVEMENT
(Shall Apply Without Modification)

SECTION 41

PAVEMENT SUBSEALING AND JACKING
(Shall Apply Without Modification)

SECTION 42

GROOVE AND GRIND PAVEMENT
(Shall Apply Without Modification)

SECTIONS 43 through 48
(Blank)

SECTION 49

PILING
(Shall Apply Without Modification)

SECTION 50

PRESTRESSING CONCRETE
(Shall Apply Without Modification)

SECTION 51

CONCRETE STRUCTURES